

# **THUNDER**

## **CENTAUR**

---

# **Weavers**

## **World**



Photographic fabric scans are not colour accurate. Always request actual fabric samples before ordering.

## SPECIFICATIONS

**Application** Contract Upholstery & Soft Seating

**Composition:** Surface 9% PU + 91% PVC

Base 95% Polyester + 5% Cotton

**Width** 140cm

**Mass** 610gm/1m

**Thickness** 1.0mm

---

		STANDARD	THUNDER
<b>Abrasion Resistance:</b>		<b>25 000 Rubs</b>	<b>&gt;100 000 Rubs</b>
	<b>EN 150 4670-2</b>		
<b>Colour Fastness:</b>			
<b>To Light</b>	<b>EN 150 105-B05</b>	<b>6</b>	<b>5</b>
<b>To Rubbing</b>	<b>EN 150 105-X12</b>	<b>4</b>	<b>4</b>
<b>Seam Slippage:</b>	<b>Warp</b>	<b>180N</b>	<b>+180N</b>
	<b>Weft</b>	<b>180N</b>	<b>+180N</b>
<b>Tensile Strength:</b>	<b>Warp</b>	<b>400N</b>	<b>+440N</b>
	<b>Weft</b>	<b>400N</b>	<b>+440N</b>

**NOTE: Refer to SABS 726 - This specification calls for a minimum seam of 15mm and 4-5 stitches per cm.**