

**VULCAN**  
**FIRE**

---

**Weavers**  
**World**



Photographic fabric scans are not colour accurate. Always request actual fabric samples before ordering.

## SPECIFICATIONS

|              |                                  |
|--------------|----------------------------------|
| Application  | Contract Upholstery & Screening  |
| Composition: | 100% Acrylic                     |
| Width        | 140cm                            |
| Mass         | 464gm/m <sup>2</sup>             |
| Complies To  | SABS 1324 Contract Specification |

---

|                       |      | STANDARD              | VULCAN       |
|-----------------------|------|-----------------------|--------------|
| Abrasion Resistance:  |      | 25 000 Rubs           | +30 000 Rubs |
| Colour Fastness:      |      |                       |              |
| To Light              |      | 6                     | +7           |
| To Rubbing            |      | 4                     | 5            |
| To Dry Cleaning       |      | 4                     | 5            |
| To Perspiration       |      | 4                     | 4-5          |
| To Pilling            |      | 4                     | 4-5          |
| Seam Slippage:        | Warp | 180N                  | 310N         |
|                       | Weft | 180N                  | 390N         |
| Tensile Strength:     | Warp | 400N                  | 920N         |
|                       | Weft | 400N                  | 740N         |
| Cleaning Instructions |      | Professional Cleaning |              |

**NOTE: Refer to SABS 726 - This specification calls for a minimum seam of 15mm and 4-5 stitches per cm.**